

# XL-6322A

## 1D Barcode Scanner



Support all kinds of 1D codes, including GS1.

Built-in high-speed ARM CPU, fast, strong performance.

Highly integrated design, 1.5m anti-drop height.

Fully compatible with all kinds of systems, plug and play.

Application in supermarkets, restaurants, office automation.



Model Number	XL-6322A	Size	L × W × H:175mm × 73mm × 102mm
Light Source	Visible Laser Diode 650nm	Weight	246g
Scan Pattern	Single Scan	Material	ABS+PC
Decode Rate	300 times/second	Voltage	5VDC
Scan Precision	3mil	Operating Current	85mA
Scan Width	30mm@scan window, 220mm@200mm	Static Current	30mA
Scan Depth of Field	0-330mm (0.33mm pcs0.9)	Laser Class	Meet the Grade I National Criteria for Laser Safety
Elevation Angle	65°	EMC	CE& FCC DOC compliance
Deflection Angle	55°	Operating Temperature	- 0°C to 50°C
Support Interface	PS-2(KB); RS-232; USB-HID; USB-Virtual COM	Storage Temperature	- 40°C to 70°C
Print Contrast	10% UPC/EAN 100%	Humidity	5% to 85% relative humidity,non-condensing
Mention Pattern	Buzzer, Indicator	Light Levels	Daylight,3000-8000LUX
Scan Mode	Automatic & Continuous & Manual	Shock	Designed to withstand 1.5M drops
Decoding Capability	EAN-8/EAN-13/UPC-A/UPC-E/Code 39/Code 93/Code 128/EAN128/Codabar/Industial 2 of 5/ Interleave 2 of 5/Matrix 2 of 5/MSI。		



**admate**  
ταμειακά συστήματα / αυτοματισμοί γραφείου  
καταμετρητές χρημάτων