

ADMATE M-820




admāte

ταμειακά συστήματα / αυτοματισμοί γραφείου
καταμετρητές χρημάτων

ΘΕΡΜΙΚΟΣ ΕΚΤΥΠΩΤΗΣ

ΑΠΟΔΕΙΞΕΩΝ - ΠΑΡΑΓΓΕΛΙΩΝ

- RS - 232 , USB, ETHERNET.
- Συμπαγής και μικρός σε μέγεθος.
- Δέχεται χαρτοταινία πλάτους 80mm
- Ανάλυση: 203 dpi
- Ταχύτητα εκτύπωσης: 260mm/s



αηδρδδδδ



iOS



Windows



Linux



ADMATE M-820



THERMAL RECEIPT PRINTER

Printing method	Direct thermal
Paper width	80mm
Print width	72mm
Column capacity	576 dots/line or 512 dots/line
Printing speed	260 mm/s Max.
Interface	USB+Serial Lan
Line spacing	5.75 mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Simplified/Traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A: 1.5•3.0mm(12•24 dots) Font B:1.1•2.1mm(9•17 dots) Simplified/Traditional Chinese: 5.0•5.0mm(2•24 dots)
Autocutter	Partial
Extension character sheet	PC547 (Standard Europe) / Katakana / PC 8 5 0 (Multilingual) / PC8 6 0 (Portugal) / PC 8 6 5 (Canadian) / PC8 6 5 (Nordic) / West Europe / Greek / Hebrew / East Europe /1ra n/WPC1252 / PC8 6 6 (Cyrillic 2) / PC8 5 2 (Latin 2) / PC8 5 8 /1ranII / Latvian / Arabic / PT151 (1251)
1D Barcode	UPC—A/ UPC— E/JAN15 (EAN15) /JAN8 (EAN8) /CODE59/ITF/CODABAR/CODE95/ CODE128
2D Barcode	QR CODE / PDF417 (Except USB+ Serial / USB / Lan)
Input buffer	128 Kbytes; 6ϕ Kbytes(USB+Serial / USB / Lan)
NV Flash	256 Kbytes
Power adaptor	Input: AC 110 -240V, 50 -6 0Hz, Output: DC 24V/2.5A
Printer Input	DC 24V/2.5A
Cash drawer	DC 24V/1A
Weight	1.0 Kg
Dimensions	19 0.15 (D)*140 (W)*15 k.64 (H) mm
Work environment	Temperature (0 -45°C) humidity(10-80%)
Storage environment	Temperature(—10 -60°C) humidity(10 -90%)
Cutter life	1.5 million cuts
Printer head life	150 Km
Emulation	ESC/ POS
Driver	Windows/JPOS/ Linux/OPOS/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS, Android, Windows



admāte
ταμειακά συστήματα / αυτοματισμοί γραφείου
καταμετρητές χρημάτων